



Quota di serraggio (Q)mm - Numero Plastre x (2.0 + sp. plastre)

N° plastre	Lunghezza Guida plastre	Lunghezza fili	Lunghezza (L)	S
5 - 136	1000 mm	1000 mm	1360 (FN 10)	30 (FN 10)
10 - 150	1500 mm	1500 mm	1500 (FN 10)	40 (FN 10)
156 - 255	1500 mm	1500 mm	1500 (FN 10)	40 (FN 10)
256 - 315	1750 mm	1500 mm	1630 (FN 10)	40 (FN 10)
316 - 01/TRE	2000 mm	2000 mm	2080 (FN 10)	

Scambiatore a Plastre - SP24TL

Q	Descrizione (denominazioni)
1	Plastre Antirisc. (base a filo)
2	1 Plastre Posizion. (base piatto)
3	1 Plastre Posizion. (base beam)
3	1 Guida-plastre alto (upper beam)
4	1 Guida-plastre basso (lower beam)
5	1 Trave M20 S118 (upper beam)
6	1 Trave M20 S118 (lower beam)
7	4 Manicella (Fornaci class. 1)
8	8 Dado M30 (N/A)
9	4 Dado M12 (N/A)
10	10 Vite resagonomia M12x20 (torx sc24w)
11	10 Vite resagonomia M12x20 (torx sc24w)
12	20
13	8 Ferramenta M20 S118 (N/A) (N/A)
14	8 Ferramenta M20 S118 (N/A) (N/A)
15	1 Rullo in resina 100X100
16	2 Plastre di supporto filo

S.T.B. DIVISIONE WINTER

STB Divisione Winter
Via Emilia 4/RP - Italia
16136 Genova - Italia
P.Iva 03102690101

STB Divisione Winter
http://www.stbitalico.com
stbitalico@stbitalico.com
Tel. +39 010 8356840
Fax +39 010 8352974

Copyright: STB Divisione Winter
Rev. 01/23

Formato	A3
Scala	1:10
Rev.	01/23