



Quota di serraggio (Q)mm - Numero Plastre x (2.6 + sp. plastre)

N° plastre	Lunghezza Guida plastre	Lunghezza filetti	Lunghezza (L)	S
5 - 136	1000 mm	1000 mm	1090 (FN 10)	40 (FN 10)
10 - 150	1500 mm	1500 mm	1580 (FN 10)	50 (FN 10)
156 - 252	1500 mm	1500 mm	1580 (FN 10)	50 (FN 10)
256 - 315	1750 mm	1750 mm	1840 (FN 10)	50 (FN 10)
316 - OLTRE	2000 mm	2000 mm	2090 (FN 10)	50 (FN 10)

Descrizione (denominazioni)

1. Plastrone Antiriscaldamento
2. 1. Plastrone Positivo (bosca piatto)
3. 1. Guida plastre alto (upper beam)
4. 1. Guida plastre basso (lower beam)
5. 1. Tirante M30 S1 B (upper beam)
6. 1. Tirante M30 S1 B (lower beam)
7. 4. Manicella (Fornace 400/2000)
8. 1/2. Dado M12 (N4)
9. 4. Dado M12 (N4)
10. 10. Vite antiscivolo M12x20 (torx 6276)
11. 20. Vite antiscivolo M12x20 (torx 6276)
12. 20. Vite antiscivolo M12x20 (torx 6276)
13. 1/2. Ferruccio M30 S1 B (N4 1500)
14. 1/2. Ferruccio M30 S1 B (N4 1750)
15. 1. Rullo in resina 100X100
16. 2. Plastre di supporto tubo

ST.B. DIVISIONE WINTER

STB Divisione Winter
Via Emilia 49/R - Italia
16136 Genova - Italia
P.iva 03102090101

<http://www.stbaitalia.com>
stbaitalia@stbaitalia.com
T. tel. +39 010 8326840
Fax +39 010 8326974

Copyright: STB Divisione Winter
Formato: A3
Scala: 1:10
d11_3385
REV. 0/33